



Combination Permeameter, 2.5" (63.4 mm)

Code: 25-0623

Product Group: Combination Permeameter Constant or Falling Head

- Plated steel chamber head assembly
- Corrosion-resistant cast aluminum base assembly
- Includes accessories for conducting both constant and falling head permeability studies

This combination permeameter has a transparent plastic chamber for soil specimens of either fine-grained or coarse-grained soils. Generally, soils containing 10 percent or more particles passing a 75 μ m sieve are tested using the falling head assembly. More granular soils, containing 90 percent or more particles retained on the 75 μ m sieve, are tested using the constant head assembly.

The cell is sealed at the top so that a vacuum may be used to saturate the specimen. Porous stones located at the top and bottom of the cell prevent sample flaking or washout. For constant head tests, a plastic funnel reservoir is mounted on an upright attached to the cell, providing a maximum head of 550 mm. Falling head tests are performed using the graduated pipette falling head reservoir, which gives a maximum head of 1000 mm and is graduated 0.2 ml.

Specification

Specimen size	63.5 x 140 mm (dia x l max)
Chamber	Transparent plastic, single section
Base	Cast aluminium
Top seal	Plated steel with gaskets
Porous Stones	62.7 x 12.7 mm (diameter x thickness)
Constant head	Plastic, funnel reservoir, 550 mm maximum head
Falling head	Graduated pipette, 100 ml x 0.2 ml, 1000 mm maximum head
Weight kg	5
Specimen Size	2-1/2" diam. x 5-1/2" l. max. (63.5 x 140 mm).
Capacity	Clear lucite; 1/4" (6.3 mm) wall; single section.
Base	Cast aluminium.
Top Seal	Plated steel with gaskets.
Porous Stones	Mounts at top and bottom;

Constant Head	2.47" diam. x 1/2" thick (62.7 x 12.7 mm); 105-120 permeability rating; 300 micron, average pore size. Plastic; funnel reservoir; 55 cm maximum head.
Falling Head	Graduated pipette; 100 mm x 0.2 mm; 100 cm. maximum head.
Weight	Net 11 lbs. (5 kg).

Spares/Consumables



Porous Stone 2.47" x .50"

Code: T-308

Alternatives



Constant Head Sand/Gravel Permeameters, 3" (76.2 mm)

Code: 25-0562